

KULATINY			
Jakost		Rozměr	
19422 / NC6 / 1.2063		fi 8,2 - 323 mm	
19572 / NC10 / 1.2201		fi 8,2 - 403 mm	
19436 / 1.2080 / NC11		fi 101,5 - 243 m	
19573 / 1.2379 / NC11LV		fi 16 - 400 mm	
19312 / 1.2842 / NMV		fi 20,5 - fi 60,8 mm	
19735/19733 / 1.2550 / NZ3		fi 19,7 - 121,5 mm	
19191 / 1.1545 / N10E		fi 25,5 - 180 mm	
19541 / 1.2343 / WCL		fi 15,5 - 400 mm	
19554 / 1.2344 / WCLV		fi 270 mm	
19541 / 1.2365 / WLV		fi 128 mm	
12312 / 1.2367		fi 150, 200 mm	
19830 / 1.3343 / SW7M		fi 10 - 150 mm	
17029 / 1.4034 / 4H13		fi 12,2 - 250 mm	
Jakost		Rozměr	
12050 / 1.0503 / C45		fi 20 - 600 mm	
11523 / S355J2G3		fi 20 - 600 mm	
14140 / 1.7035 / 40H		fi 20 - 280 mm	
15142 / 1.7225 / 40HM		fi 20 - 600 mm	
15142.6 / 1.7225 / 40HM-T		fi 20 - 650 mm	
16343.6 / 1.6582 / 34HNM QT		fi 25 - 65 mm	
16343 / 1.6582 / 34HNM		fi 25 - 330 mm	
14220 / 1.7131 / 16HG		fi 20 - 350 mm	
15260 / 1.8159 / 50HF		fi 16 - 160 mm	
35HGSA		fi 20 - 180 mm	
15340 / 1.8509 / 38HMJ		fi 30,8 - 200 mm	

PLOCHÁ OCEL		
Jakost	Tloušťka	Šířka
19422 / NC6 / 1.2063	10-80 mm	30-600 mm
19572 / NC10 / 1.2201	16-300 mm	40-600 mm
19436 / 1.2080 / NC11	20-80 mm	100-500 mm
19573 / 1.2379 / NC11LV	12-300 mm	80-600 mm
19735/19733 / 1.2550 / NZ3	16-80 mm	60-250 mm
19552 / 1.2343 / WCL	30-400 mm	150-1000 mm
19554 / 1.2344/WCLV	300 mm	1000 mm
19520 / 1.2311 QT	20-185 mm	150-600 mm
1.2312 QT	20-400 mm	250-1000 mm
1.2738 QT 36-40 HRC	255-400 mm	1000-2500 mm
1.2316 QT	300 mm	800 mm
1.2083 / 4H13	20-120 mm	400-600 mm
14140 / 1.7035 / 40H	16-200 mm	40-200 mm
12050 / C45	20-80 mm	200-600 mm

PLECHY			
Jakost	Tloušťka	Šířka	Délka
12050 / C45	1-300 mm	1000-2000 mm	2000-6000 mm
11523 / S355J2+N	20-150 mm	1960-2000 mm	3000-6000 mm
14220 / 16MnCr5/16 HG	16-60 mm	2000 mm	6000 mm
14140 / 41Cr4/40H	3-80 mm	1000-2000 mm	2000-6000 mm
15142 / 42CrMo4/40HM	10-160 mm	2000 mm	3500-6000 mm
15260 / 50CrV4/50HF	0,5-12 mm	1000-2000 mm	2000-6000 mm
19520 / 1.2311 QT	25-185 mm	1600-2000 mm	3020-6000 mm
1.2312 QT	20-80 mm	2000-2050 mm	3000-6000 mm
NICRODUR/ABRAZO/HARDOX 400	8-60 mm	2000 mm	6000 mm
NICRODUR/ABRAZO/HARDOX 500	8-40 mm	2000 mm	6000 mm
19312 / 1.2842 / NMV	8-120 mm	503-603 mm	2500-4000 mm
S690QL	10-55 mm	1500-2000 mm	5800-6000 mm

KULATINY (tažený stav)	
Jakost	Rozměr
S355JR tolerance H9/H11	fi 20-50 mm

PÁSY		
Jakost	Tloušťka	Šířka
15260 / 50CrV4	0,3-0,8 mm	100-200 mm
12071 / C67	0,2-1,1 mm	7-350 mm